

Weather Resistant High Power Sound Columns

S0904 8 Ohm 30W White

S0905 8 Ohm 30W Black

S0907 100V 30W White

S0908 100V 30W Black



S0904

S0905


Can be vertically or horizontally mounted



All models include the unique Wacki® bracket, making installation a breeze.



Angle Option For Wacki® Bracket: For installations requiring additional degree of angle adjustment.



100V models are supplied with multi-core cable connected to the various power taps of the transformer for easy installation.

Weather Resistant Sound Monitors

IP54 Rated for use in sheltered outdoor applications

These sound monitors are constructed from super tough UV stabilised 'Luran-S' thermoplastic. They feature a two way, bass reflex speaker system with a 100mm bass/midrange driver and a polyimide dome tweeter with a custom designed crossover network. They produce a punchy, powerful sound making them the perfect choice for BGM/paging applications in hotels, taverns, shopping centres, halls, schools, and fairgrounds. Included is the revolutionary Wacki bracket mounting system, allowing a wide variation in mounting angles. Available in either 8Ω or 100V line in white or black.

Some applications include: • Home stereo extension speakers for pool, patio etc. • Taverns, hotels, shopping centres, schools, halls, fairgrounds and all external music and paging applications

FEATURES

Weather resistant
High impact UV stabilised 'Luran S' thermoplastic
Engineer designed in Australia

Ported and tuned enclosure for enhanced response
Includes polyswitch overload protection
Supplied complete with Wacki mounting bracket

Electronic Specifications

Power rating (8Ω models):	30 watts
Power taps (100V models):	.5, 10, 20, 30 watts
SPL 1W @ 1m:	.91dB
Freq response:	.90Hz- 18kHz
Dimensions:	≈230H x 155W x 115D mm

*Specifications subject to change without notice

Manufactured in Australia

Distributed By:



Email : info@qmax.net.au

Internet : www.qmax.net.au

Phone : +61 8 9455 4671

Fax : +61 8 6210 1749